



"THIS DRAWING, ENGINEERING REPORT OR DOCUMENT IS COPYRIGHT AND PROPERTY IS RESERVED THEREIN AND THE INFORMATION CONTAINED THEREIN IS CONFIDENTIAL. THIS DRAWING, ENGINEERING REPORT OR DOCUMENT AND INFORMATION MAY NOT BE REPRODUCED OR COMMUNICATED TO A THIRD PARTY OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IS SUPPLIED WITHOUT THE PRIOR WRITTEN CONSENT OF PETER JACKMAN."



THIRD ANGLE PROJECTION

A3



ITEM NO.	PART / DRAWING	QTY.
1	SR U-VAN AXLE GUARD PAIR	1
2	SR U-VAN BRAKE GEAR	2
3	BACK-BACK SPACER	1
4	SR U-VAN WHEEL G1 34,1mm	2
5	AXLE TUBE ALBION ALLOYS, BT3M	1
6	3X6X2,5 63ZZ BRG	2
7	DIN 7991 - M3 x 8 --- 4.8N	2
8	S UT-VAN BRAKE SHOE BEAM	2
9	BRAKE BLOCK PIN (1mm Brass)	4

ASSEMBLY

1. - GLUE BRAKE GEAR (2) INTO AXLE GUARD PAIR (1) USE SUPER GLUE OR MEK DEPENDING ON MATERIAL CHOSEN FOR PARTS AND ALLOW TO DRY.
- 2 - LOCATE WHEELS (4), BACK-BACK SPACER (3) AND AXLE TUBE (5) IN POSITION.
- 3 - INSERT BEARINGS (6) AROUND AXLE TUBE ENDS AND INSIDE AXLE GUARDS (1). USE SCREWS (7) OR TEMPORARILY LONGER TO PULL BEARINGS INTO POSITION.
- 4 - ENSURE FREE RUNNING BY ROLLING ASSEMBLY ALONG BENCH TOP. A DROP OF LIGHT OIL ON THE OUTSIDE OF THE BEARING SHIELDS WORKED IN WILL HELP ALIGN BEARINGS.
- 5 - FIT BRAKE SHOE BEAMS (8) AND RETAIN WITH PINS (9).

DIMENSIONS mm				
ESTIMATED MASS g	MATERIAL MAINLY 3D PRINTED	DESCRIPTION UTILITY VAN W FRAME ASSY		
SCALE VARIOUS	FINISH	Made From SEE ITEM LIST	PART/Drg. SR U-VAN WFRAME ASSY	SHEET 1 OF 1

ISS.	DATE	DRAWN
A	21/07/2026	P.R.J.